

# TECHNICAL PARAMETER

Power: AC110V-240V 50-60Hz  
 Lamp: HNI575W  
 Consumption: 680W  
 Control: DMX 512  
 Channels: 8CH  
 Size: 500×470×565mm  
 N.W: 31kg  
 G.W: 34kg



## 通道功能 channel function

1	Color Wheel 1	0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100
2	Color Wheel 2	0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100
3	Atomization	0 255
4	Strobe	0 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 95 100 240 245 250 255
5	X 軸 Pan	0 255
6	Y 軸 Tilt	0 255
7	X/Y Speed	0 255
8	Reset	0 255

## PERFORMANCE TRAIT

4 colors+white, with high speed and rainbow effect  
 0-100% mechanical linear dimmer and  
 1-10 times/s high speed strobe effect  
 Pan 450° and tilt 270° ,  
 smooth scanning and accurate orientation  
 Precise and speed can adjustment on pan and tilt  
 3 primary color effect(C.M.Y.K)  
 3 primary speed adjustment  
 Built-in over heat protection and high  
 voltage protection  
 Compatible with DMX 512 international digital signal  
 According to various kinds of safety standards,  
 Ip20 protect grades,  
 the cable accords to  
 the CE20/22 standard

